# SILICONE SHINE



#### PRODUCT OVERVIEW

A light and fruity fragranced polish for internal and external automotive non-porous surfaces. Can also be used as a light duty lubricant for metal, plastic and rubber parts.

#### FEATURES AND BENEFITS

- Freshens and shines.
- Reduces friction.
- Helps prevent cracking / premature ageing of rubbers.
- Fast acting, virtually instantaneous evaporation.

#### TYPICAL APPLICATIONS

This product is designed for use on laminates, polyurethane, chromium, carbon fibre and other polymeric materials.

#### **DIRECTIONS FOR USE**

Shake thoroughly before use. Apply from a distance of 10 - 20cm, and wipe the surface with a soft cloth. To avoid overspray this product may be applied directly to a cloth.

### WHERE NOT TO USE

- · On any area where increased slip would create hazards, i.e. steering wheels, foot pedals, rubber foot mats etc.
- On glass or clear plastics where smearing may occur.
- On surfaces likely to be painted.

#### TECHNICAL DATA

## PHYSICAL PROPERTIES

Appearance A colourless liquid with a fruity fragrance.

pH Not applicable
Specific Gravity [Base] 0.788 - 0.808
Viscosity Thin liquid

Flammability, as supplied Extremely Flammable, flash point below -20°C

Composition Data, as supplied A solution of silicone fluids and synthetic fragrance in hydrocarbon

solvents and a butane/propane/iso-butane based propellant.

Application Temperature Ambient temperatures.

Availability 400ml Aerosols.



